










| Item | Part number  | Description                                   | Contacts   | Connector type | Mounting type       | Contact supplied | Material                           | Electrical data | Temperature rating | Illustrative picture  |   |
|------|--|---|------------|----------------|---------------------|------------------|------------------------------------|-----------------|--------------------|---|---|
| 1    | M24308/4-1F  | Standard Density D-SUB Connector - Male       | 9          | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |     |   |
| 2    | M24308/4-2F  | Standard Density D-SUB Connector - Male       | 15         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 3    | M24308/4-3F  | Standard Density D-SUB Connector - Male       | 25         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 4    | M24308/4-4F  | Standard Density D-SUB Connector - Male       | 37         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 5    | M24308/4-5F  | Standard Density D-SUB Connector - Male       | 50         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 6    | M24308/2-1F  | Standard Density D-SUB Connector - Female     | 9          | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |  |
| 7    | M24308/2-2F  | Standard Density D-SUB Connector - Female     | 15         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 8    | M24308/2-3F  | Standard Density D-SUB Connector - Female     | 25         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 9    | M24308/2-4F  | Standard Density D-SUB Connector - Female     | 37         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 10   | M24308/2-5F  | Standard Density D-SUB Connector - Female     | 50         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 11   | M24308/4-11F   | High Density D-SUB Connector - Male           | 15         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |    |   |
| 12   | M24308/4-12F   | High Density D-SUB Connector - Male           | 26         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 13   | M24308/4-13F   | High Density D-SUB Connector - Male           | 44         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 14   | M24308/4-14F   | High Density D-SUB Connector - Male           | 62         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 15   | M24308/4-15F   | High Density D-SUB Connector - Male           | 78         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 16   | M24308/4-16F   | High Density D-SUB Connector - Male           | 104        | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |  |
| 17   | M24308/2-11F   | High Density D-SUB Connector - Female         | 15         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 18   | M24308/2-12F   | High Density D-SUB Connector - Female         | 26         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 19   | M24308/2-13F   | High Density D-SUB Connector - Female         | 44         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 20   | M24308/2-14F   | High Density D-SUB Connector - Female         | 62         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 21   | M24308/2-15F   | High Density D-SUB Connector - Female         | 78         | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |   |   |
| 22   | M24308/2-16F   | High Density D-SUB Connector - Female         | 104        | Rectangular    | Cable               | Yes              | Steel with cadmium plating         | 375V R.M.S.     | 125°C              |    |   |
| 23   | D38999/26FB35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 13         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 24   | D38999/26FC35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 22         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 25   | D38999/26FD35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 19         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 26   | D38999/26FE35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 55         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 27   | D38999/26FF35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 66         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 28   | D38999/26FG35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 79         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 29   | D38999/26FH35PN  | Circular Connector, MIL-DTL-38999 S3 - Male   | 100        | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |  |
| 30   | D38999/26FB35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 13         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 31   | D38999/26FC35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 22         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 32   | D38999/26FD35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 19         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 33   | D38999/26FE35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 55         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 34   | D38999/26FF35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 66         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 35   | D38999/26FG35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 79         | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| 36   | D38999/26FH35SN  | Circular Connector, MIL-DTL-38999 S3 - Female | 100        | Circular       | Cable               | Yes              | Aluminum Alloy with nickel plating | 1300 V R.M.S.   | 200°C              |   |   |
| Item | Part number  | Description                                   | Cable Exit | Cable Type     | Number of Positions | Cable diameter   | Material                           | -               | Temperature rating | Illustrative picture  |   |
| 37   | L17DTZK-09-K   | Backshell SD/HD D-Sub                         | 180°       | Round          | 9                   | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |  |   |
| 38   | L17DTZK-15-K   | Backshell SD/HD D-Sub                         | 180°       | Round          | 15                  | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |   |   |
| 39   | L17DTZK-25-K   | Backshell SD/HD D-Sub                         | 180°       | Round          | 25                  | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |   |   |
| 40   | L17DTZK-37-K   | Backshell SD/HD D-Sub                         | 180°       | Round          | 37                  | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |   |   |
| 41   | L17DVZK-09-K   | Backshell SD/HD D-Sub                         | 45°        | Round          | 9                   | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |  |   |
| 42   | L17DVZK-15-K   | Backshell SD/HD D-Sub                         | 45°        | Round          | 15                  | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |   |   |
| 43   | L17DVZK-25-K   | Backshell SD/HD D-Sub                         | 45°        | Round          | 25                  | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |   |   |
| 44   | L17DVZK-37-K   | Backshell SD/HD D-Sub                         | 45°        | Round          | 37                  | 3 - 13 mm        | Zinc die-cast, nickel plated       | -               | 120°C              |   |   |
| Item | Part number  | Description                                   | Cable Exit | Mating Style   | Shell Size          | Cable opening    | Material                           | -               | -                  | Illustrative picture  |   |
| 45   | M85049/38S11N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 11                  | 3.81mm - 5.84mm  | Aluminum Alloy, nickel plated      | -               | -                  |  |   |
| 46   | M85049/38S13N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 13                  | 4.83mm - 8.38mm  | Aluminum Alloy, nickel plated      | -               | -                  |   |   |
| 47   | M85049/38S15N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 15                  | 6.60mm - 11.68mm | Aluminum Alloy, nickel plated      | -               | -                  |   |   |
| 48   | M85049/38S17N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 17                  | 7.11mm - 15.49mm | Aluminum Alloy, nickel plated      | -               | -                  |   |   |
| 49   | M85049/38S19N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 19                  | 8.25mm - 16.10mm | Aluminum Alloy, nickel plated      | -               | -                  |   |   |
| 50   | M85049/38S21N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 21                  | 8.71mm - 17.73mm | Aluminum Alloy, nickel plated      | -               | -                  |   |   |
| 51   | M85049/38S23N  | backshell MIL-DTL-38999                       | 180°       | Self Locking   | 23                  | 9.68mm - 20.90mm | Aluminum Alloy, nickel plated      | -               | -                  |   |   |
| 52   | MOQ for connectors and backshells is 1 piece. Other types of rectangular and circular connectors and backshells are available on request. In case of any requirement please contact our company. |   |            |                |                     |                  |                                    |                 |                    |   |   |