










Item	Part number	Description	Conductor count	AWG	Shield	Jacket / Insulation	Electrical data	Temperature rating	Illustrative picture	
1	M27500-12TG2T14	Twisted Pair Wire, shielded	2	12	T - Single TPC Round	Single Extruded White ETFE	600 Volts R.M.S.	150°C		
2	M27500-20SB2T23	Twisted Pair Wire, shielded	2	20	T - Single TPC Round	Extruded - White - Modified XLETFE	600 Volts R.M.S.	200°C		
3	M27500-22SB2T23	Twisted Pair Wire, shielded	2	22	T - Single TPC Round	Extruded - White - Modified XLETFE	600 Volts R.M.S.	200°C		
4	M27500-24SB2T23	Twisted Pair Wire, shielded	2	24	T - Single TPC Round	Extruded - White - Modified XLETFE	600 Volts R.M.S.	200°C		
5	M27500-26SB2T23	Twisted Pair Wire, shielded	2	26	T - Single TPC Round	Extruded - White - Modified XLETFE	600 Volts R.M.S.	200°C		
6	M27500-28SB2T23	Twisted Pair Wire, shielded	2	28	T - Single TPC Round	Extruded - White - Modified XLETFE	600 Volts R.M.S.	200°C		
7	M27500-20SB2U00	Twisted Pair Wire	2	20	No shield	No jacket	600 Volts R.M.S.	150°C		
8	M27500-22SB2U00	Twisted Pair Wire	2	22	No shield	No jacket	600 Volts R.M.S.	150°C		
9	M27500-24SB2U00	Twisted Pair Wire	2	24	No shield	No jacket	600 Volts R.M.S.	150°C		
10	M27500-26SB2U00	Twisted Pair Wire	2	26	No shield	No jacket	600 Volts R.M.S.	150°C		
11	M27500-28SB2U00	Twisted Pair Wire	2	28	No shield	No jacket	600 Volts R.M.S.	150°C		
12	M22759/16-20-9	Single tin plated copper wire, white	1	20	No shield	Single Layer of Extruded ETFE	600 Volts R.M.S.	150°C		
13	M22759/16-22-9	Single tin plated copper wire, white	1	22	No shield	Single Layer of Extruded ETFE	600 Volts R.M.S.	150°C		
14	M22759/16-24-9	Single tin plated copper wire, white	1	24	No shield	Single Layer of Extruded ETFE	600 Volts R.M.S.	150°C		
15	M22759/32-26-9	Single tin plated copper wire, white	1	26	No shield	Cross Linked ETFE	600 Volts R.M.S.	150°C		
16	M22759/32-28-9	Single tin plated copper wire, white	1	28	No shield	Cross Linked ETFE	600 Volts R.M.S.	150°C		
17	NF24Q100	Quadrax Ethernet cable	4	24	Tin-coated Copper Flat Braid	Extruded Expanded PTFE	Impedance 100 ohms	150°C		
18	M17/128-RG400	Coax Cable	1	-	Two SPC braided shields	Fluorinated Ethylene Propylene	Impedance 50 ohms	392°C		
Item	Part number	Description	Color	AWG	Material	Single wire	Multiple wire range	Temperature rating	Illustrative picture	
19	M81824/1-1	MiniSeal splice	Red	26-20	Polyvinylidene Fluoride	26-24-22-20	0.15 - 0.75 mm <sup>2</sup>	150°C		
20	M81824/1-2	MiniSeal splice	Blue	20-16	Polyvinylidene Fluoride	20-18-16	0.53 - 1.34 mm <sup>2</sup>	150°C		
Item	Part number	Description	Inner diameter	Size	Material	Minimum coverage			Illustrative picture	
21	RAY-101-4.0	Shield Braid	4.0 ± 0.25 mm	36/0.13	Tin plated copper	93%	-	-		
22	RAY-101-10.0	Shield Braid	10.0 ± 0.25 mm	36/0.13	Tin plated copper	93%	-	-		
Item	Part number	Description	Color	Size	Material	Inside Diameter	Recovered Diameter	Temperature rating	Illustrative picture	
23	RNF-100-1/16-0	Heat Shrink Tubing	Black	1/16	Polyolefin (PO)	1.6	0.8	135°C		
24	RNF-100-3/32-0	Heat Shrink Tubing	Black	3/32	Polyolefin (PO)	2.4	1.2	135°C		
25	RNF-100-1/8-0	Heat Shrink Tubing	Black	1/8	Polyolefin (PO)	3.2	1.6	135°C		
26	RNF-100-3/16-0	Heat Shrink Tubing	Black	3/16	Polyolefin (PO)	4.8	2.4	135°C		
27	RNF-100-1/4-0	Heat Shrink Tubing	Black	1/4	Polyolefin (PO)	6.4	3.2	135°C		
28	RNF-100-3/8-0	Heat Shrink Tubing	Black	3/8	Polyolefin (PO)	9.5	4.8	135°C		
29	RNF-100-1/2-0	Heat Shrink Tubing	Black	1/2	Polyolefin (PO)	12.7	6.4	135°C		
30	RNF-100-3/4-0	Heat Shrink Tubing	Black	3/4	Polyolefin (PO)	19.1	9.5	135°C		
31	RNF-100-1-0	Heat Shrink Tubing	Black	1	Polyolefin (PO)	25.4	12.7	135°C		
32	RNF-100-1-1/4-0	Heat Shrink Tubing	Black	1-1/4	Polyolefin (PO)	31.8	15.9	135°C		
33	RNF-100-1-1/2-0	Heat Shrink Tubing	Black	1-1/2	Polyolefin (PO)	38.1	19.1	135°C		
34	RW-175-1/16-X	Heat Shrink Tubing	Clear	1/16	Polyvinylidene Fluoride	1.6	0.8	175°C		
35	RW-175-3/32-X	Heat Shrink Tubing	Clear	3/32	Polyvinylidene Fluoride	2.4	1.2	175°C		
36	RW-175-1/8-X	Heat Shrink Tubing	Clear	1/8	Polyvinylidene Fluoride	3.2	1.6	175°C		
37	RW-175-3/16-X	Heat Shrink Tubing	Clear	3/16	Polyvinylidene Fluoride	4.8	2.4	175°C		
38	RW-175-1/4-X	Heat Shrink Tubing	Clear	1/4	Polyvinylidene Fluoride	6.4	3.2	175°C		
39	RW-175-3/8-X	Heat Shrink Tubing	Clear	3/8	Polyvinylidene Fluoride	9.5	4.8	175°C		
40	RW-175-1/2-X	Heat Shrink Tubing	Clear	1/2	Polyvinylidene Fluoride	12.7	6.4	175°C		
41	RW-175-3/4-X	Heat Shrink Tubing	Clear	3/4	Polyvinylidene Fluoride	19.1	9.5	175°C		
42	RW-175-1-X	Heat Shrink Tubing	Clear	1	Polyvinylidene Fluoride	25.4	12.7	175°C		
43	RW-175-1-1/2-X	Heat Shrink Tubing	Clear	1-1/2	Polyvinylidene Fluoride	38.1	19.1	175°C		
44	MOQ for conductors is 10m and for accessories is 1m. Other types of wires and accessories are available on request. In case of any requirement please contact our company.									